



BURR KING® ADVANTAGE

Value Adding Accessories & Options

PEDESTAL STANDS

Burr King heavy duty pedestals are designed to position grinding and polishing machines at a convenient operator height of 33". They must be securely bolted to the floor.

Model BK-746
(Without Adapter Plate)
Model BK-746A
(As shown with Adapter Plate)

Machines which use adapter plate include: 482, 562, 600, 760, and 800.

Machines that do not need the adapter plate include: 720, 960, 1000, 1200 and 1272.



VARI-SPEED MOTORS/ CONTROLLERS



The variable speed motor option is available on all Burr King models. Surface speeds from 800 to 8000 S.F.P.M. are obtainable. The variable speed motor controls temperature, cutting action, and finish to achieve desired results.

The adjustable speed motor controller supplies constant torque, has solid state controls, on/off switch, power light indicator with dial speed control.

MAGNETIC STARTERS

Magnetic starters provide low voltage and lost phase protection. They are recommended for all three phase machines. Magnetic starters protect motors from harmful currents, overloads, and excessive temperature rise. Machines may be ordered with a magnetic starter factory installed. Factory installed starters are securely bracket mounted or provided with an umbilical suitable for mounting the starter on a wall or post. Consult with the factory for the proper starter/motor and installation combination.

NOTE: Factory warranty may be voided if magnetic starter is not used with 3 phase models.

